


PATENT
13346.0022.NPUS01

APPLICATION FOR UNITED STATES LETTERS PATENT
for
RETRACTABLE FIBER OPTIC CONNECTOR HOUSING

by
John Ehrenreich
Mike Dahan

EXPRESS MAIL MAILING LABEL	
NUMBER	<u>EL831849522 US</u>
DATE OF DEPOSIT	<u>2/27/04</u>
I hereby certify that this paper or fee is being deposited with the United States Postal Service "EXPRESS MAIL POST OFFICE TO ADDRESSEE" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to: Mail Stop Nonprovisional Application, Commissioner for Patents, PO Box 1450, Alexandria, VA 22313-1450.	
	
Signature	

PRIORITY CLAIM

This application claims the benefit of United States Provisional Patent Application Serial No. 60/450,610 filed on February 28, 2003, which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

The present disclosure relates to a fiber optic connector used for data communication and telecommunication applications, and particularly to a fiber optic connector that is easier to install and remove from a receptacle in high-density installations.

Optical fibers are an integral part of modern signal transmission systems. Optical fiber connectors are used to connect optical fibers to various receptacles, such as connecting segments of fibers together to make longer lengths, connecting fibers to active devices such as radiation sources, detectors, and amplifiers, and connecting fibers to passive devices such as switches, dividers, and attenuators. The connection between a pair of optical fiber ends typically consists of a pair of ferrules, small capillary cylinders made of glass, ceramic, or plastic fiber, which are butted together end-to-end in a manner that allows light to travel from one to the other along their common central axis. As such, optical fiber connectors perform three basic functions:

1. Provide accurate positioning and abutment of the two ferrules;
2. Provide maximum transfer of optical signals with minimal signal loss; and
3. Provide a stable mechanical joint with the receptacle so that no unintended decoupling occurs.

Optical fiber connectors are known in the art. One type of conventional connector is described in detail in U.S. Patent No. 5,481,634 to Anderson et al., which is herein incorporated by reference. The connector disclosed in that patent comprises a cylindrical ceramic ferrule, which protrudes through an opening in a plastic housing body. A

1 cylindrical spring surrounds the ferrule and interacts with an interior surface of the
2 housing body to urge the ferrule axially outward from the housing opening. The housing
3 body has a cantilever-type spring latch located on one exterior side of the connector
4 which is manually operable and which mates with a shoulder within the receptacle to lock
5 the connector therein. When a connection is made, the ferrule first seats on the optical
6 interface of the mating ferrule or active device. The housing body then continues to
7 advance until the cantilever latch clears the latching shoulder on the receptacle. The
8 internal spring absorbs this additional axial advance, and continues to apply axial force
9 between the latch and the receptacle to maintain intimate contact at the optical interface.

10 The connector of the referenced patent is but one type of fiber optic connector.
11 ST, SC, VF 45, and MTRJ connectors are also commonly used in fiber optic systems.
12 With the increasing use of optical fibers as transmission media, the general design
13 concept behind the development of the connector described above was to create a simple
14 device that could achieve higher density installations, i.e. more tightly spaced fiber optic
15 connections. One feature of such connectors that prevents maximum packing density is
16 the latching mechanism. Although advertised as easily removable by using only the tip of
17 the finger on the latching mechanism, this in reality is only true when the connector is
18 relatively unobstructed. To achieve the maximum packing configurations for which the
19 connector was designed to achieve, it is far more difficult and perhaps impossible for an
20 operator to remove a connector in a high density installation without grasping the
21 connector body and latch, or by using some other tool to depress the latch. It is still
22 highly desirable to provide a fiber optic connector that facilitates the easy installation and

1 the easy removal of the connector in a variety of installation configurations, including
2 high-density installations.

3

4

SUMMARY OF THE DISCLOSED SUBJECT MATTER

The subject matter of this disclosure overcomes the above-discussed shortcomings and satisfies a significant need for a fiber optic connector that can be more easily removed from fiber optic receptacles in high-density installations. One fiber optic connector constructed in accordance with certain teachings herein has a connector body, a latch attached to the connector body and capable of coupling with a fiber optic receptacle, and a movable latch pull having a cavity capable of at least partially enclosing the latch and at least one inclined plane that is slidable against the latch. The latch pull is engaged to the connector body in a manner so as to allow the latch pull to slide over the connector body. By moving the latch pull away from the fiber optic receptacle, at least one inclined plane of the latch pull slides against the latch, thus forcing the latch into a position closer to the connector body, thereby decoupling the latch from the fiber optic receptacle.

Another illustrative embodiment provides a strain relief boot affixed to the latch pull, whereby moving the strain relief boot away from the fiber optic receptacle forces the latch into a position closer to the connector body, thus decoupling the connector body from the fiber optic receptacle.

Alternate latching mechanisms are also provided. One embodiment utilizes a latch that is biased into a position close to the connector body. Another embodiment utilizes a latch that is connected to the connector body by means of a hinging mechanism. In both of these embodiments, by moving the latch pull towards the fiber optic receptacle, at least one inclined plane of the latch pull slides against the latch, thus forcing the latch into a position away from the connector body, and into a coupling position with the fiber

1 optic receptacle. The inclined planes are also oriented so as to allow the latch to return to
2 a position closer to the connector body when the latch pull is moved away from the fiber
3 optic receptacle, thus decoupling the latch from the fiber optic receptacle.

4

5

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the disclosed subject matter may be obtained with reference to the accompanying drawings:

Figure 1 is a perspective view of one embodiment of a fiber optic connector in accordance with certain teachings of the present disclosure, cantilever beam latch biased down, shown in a fully latched configuration, with an alternate embodiment duplex design shown in phantom.

Figure 2 is a cross-sectional perspective view of another embodiment of a fiber optic connector in accordance with certain teachings of the present disclosure, cantilever beam latch biased down, shown in a fully latched configuration.

Figure 3 is an exploded perspective view of one embodiment of a fiber optic connector in accordance with certain teachings of the present disclosure, cantilever beam latch biased down.

Figure 4 is a cross-sectional side view of a preferred embodiment fiber optic connector in accordance with certain teachings of the present disclosure, cantilever beam latch biased up, shown fully latched with a receptacle.

Figure 5 is a cross-sectional side view of a preferred embodiment fiber optic connector in accordance with certain teachings of the present disclosure, cantilever beam latch biased up, shown partially retracted from a receptacle.

Figure 6 is a perspective view of one embodiment of the latch pull mechanism in accordance with certain teachings of the present disclosure, cantilever beam latch biased up, shown in a fully latched position.

1 Figure 7A is a perspective view of another embodiment of the latch pull
2 mechanism in accordance with certain teachings of the present disclosure, cantilever
3 beam latch biased up, shown in a retracted configuration.

4 Figure 7B is a perspective view of the latch pull mechanism of Figure 7A, shown
5 in a fully latched configuration.

6 Figure 8 is an exploded perspective view of an alternate embodiment of the latch
7 pull mechanism in accordance with certain teachings of the present disclosure, hinged
8 latch.

9 Figure 9 is a perspective view of another alternate embodiment of the latch pull
10 mechanism in accordance with certain teachings of the present disclosure, cantilever
11 beam latch biased down and located on the latch pull mechanism.

12

13

DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

The present disclosure will now be described more fully with reference to the accompanying drawings in which a preferred embodiment of the invention is shown.

This disclosure may, however, be embodied in many different forms and should not be construed as being limited to the embodiment set forth herein.

Referring to Figures 1-3, there is shown a preferred embodiment of a fiber optic connector in accordance with certain teachings of the present disclosure. Fiber optic connector 100 consists of a connector body 102 which is of material injection molded plastic or any other suitable material known in the art. The connector body 102 encloses the fiber optic ferrule, stem, and spring (not shown). The spring push 104 is affixed into the connector body 14 using mechanical latches 106 to remain attached during usage – this member holds the ferrule, stem and spring into the connector body 102.

Fiber optic connector 100 also consists of a latch pull 108 having a cavity 110 capable of at least partially enclosing latch 112. Latch pull 108 is of a material injection molded plastic or any other suitable material known in the art. Latch 112 is preferably a cantilever beam of the type and material typically found in the prior art, and is attached to connector body 102. Latch pull 108 is installed over the spring push 104 and the latch 112 in a manner so as to allow the latch pull 108 to freely slide over at least a portion of the connector body 10, including at least a portion of latch 112. Latch pull 108 has at least one, and preferably, a plurality of inclined planes 114 within cavity 110, which are designed to contact and slide against latch 112. Latch 112 may slide directly against

1 inclined planes 114, or, as shown in Figures 1-3, latch 112 may contain two matched tabs
2 116 designed to contact and slide against inclined planes 114.

3 Figures 1-3 depict a preferred latch embodiment in accordance with certain
4 teachings of the present disclosure. Cantilever beam latch 112 is biased in a downward
5 direction such that inclined planes 114 force latch 112 into a position away from the
6 connector body 102 when connector 100 is latched with a fiber optic receptacle (not
7 shown). Latch 112 slides along inclined planes 114 when the latch pull is moved towards
8 connector body 102, thereby moving latch 112 and locking tabs 117 against the locking
9 surface of the fiber optic receptacle, thereby coupling connector 100 with the receptacle.
10 When latch pull 108 is moved away from the fiber optic receptacle, latch 112 slides along
11 inclined planes 114 and returns to a position closer to the connector body 102, thereby
12 releasing connector 100 from the fiber optic receptacle.

13 As is evident from this description and from the drawings, latch pull 108 enables
14 the operator to install and remove fiber optic connector 100 from a fiber optic receptacle
15 without requiring room for the operator's fingers to directly release latch 112. Rather, the
16 operator need only be able to pull the latch pull 108 away from the receptacle to release
17 fiber optic connector 100. Additionally, it is a preferred embodiment that a strain relief
18 boot 118 be permanently affixed to latch pull 108. This allows the strain relief boot 118
19 to transfer any pulling forces to latch pull 108 and thus subsequently release the fiber
20 optic connector 100 from the fiber optic receptacle. The strain relief boot 118 provides
21 even easier access and even easier removal of fiber optic connector 100 since the operator

1 must only be able to reach strain relief boot 118 and pull it away from the receptacle to
2 release fiber optic connector 100.

3 Figure 1 also illustrates an alternative embodiment in which a duplex connector
4 (the duplex portion shown as phantom 101) is provided in accordance with certain
5 teachings of the present disclosure. Duplex connectors are well known in the art and may
6 utilize the latch pull concept presented herein, although several latch pull designs are
7 envisioned. One illustrative embodiment is shown in Figure 1 in which the duplex
8 connector 101 utilizes a single latch pull to detach the duplex latches.

9 Figures 4-7 depict the alternative embodiment of the latch and latch pull
10 mechanism in which the cantilever beam latch 112 is biased in an upward direction.
11 When latch pull 108 is moved away from the fiber optic receptacle as shown in Figure 5,
12 latch 112, and more specifically latch tabs 116, slides along inclined planes 114 and is
13 forced into a position closer to the connector body 102, thereby providing the clearance
14 for latch 112 and locking tabs 117 to clear the locking surface 122 of the fiber optic
15 receptacle 120, thereby releasing connector 100 from fiber optic receptacle 120. Figures
16 4-6 depict one illustrative embodiment of inclined planes 114 where inclined planes 114
17 begin at the face of the latch pull. Figures 7A and 7B depict a second illustrative
18 embodiment for this latch pull mechanism in which entrance planes 124 are used to help
19 ensure proper latching of latch pull 108. As shown in Figure 7A, latch 112 is forced
20 downward as latch pull 108 is moved towards the connector body 102. As shown in
21 Figure 7B, latch 112 substantially returns to its biased position, which corresponds to the
22 position in which latch 112 and locking tabs 117 are locked in fiber optic receptacle 120.

1 Figure 8 shows an alternative latch embodiment in which latch 112 is attached to
2 connector body 102 using a hinging mechanism 126. As in the preferred embodiment
3 (cantilever beam latch biased down) previously described in relation to Figures 1 and 2,
4 latch 112 slides along inclined planes 114 when the latch pull is moved towards
5 connector body 102, thereby moving latch 112 and locking tabs 117 against the locking
6 surface of the fiber optic receptacle, thereby coupling connector 100 with the receptacle.
7 When latch pull 108 is moved away from the fiber optic receptacle, latch 112 slides along
8 inclined planes 114 and returns to a position closer to the connector body 102, thereby
9 releasing connector 100 from the fiber optic receptacle.

10 Figure 9 shows yet another alternative embodiment of the present disclosure in
11 which latch 128 is connected to latch pull 132. In this configuration, latch 128 is biased
12 downward and extends in the direction of connector body 102 and fiber optic receptacle
13 120. Connector body 102 has at least one, and preferably, a plurality of inclined planes
14 130, which are designed to slide against latch 128. In this embodiment, inclined planes
15 130 force latch 128 away from latch pull 132 when latch pull 132 is moved towards
16 connector body 102, thereby providing the necessary means for latch 128 and locking tabs
17 117 to couple with receptacle 120. Inclined planes 130 also allow latch 128 to return to
18 its biased position closer to latch pull 132 when latch pull 132 is moved away from fiber
19 optic receptacle 120, thereby decoupling latch 128 from fiber optic receptacle 120.

20 It is a preferred aspect of the present disclosure that all of the fiber optic
21 connectors described herein are fully compatible with fiber optic receptacles designed for
22 conventional connectors such as an "LC" connector. However, it is also envisioned that

1 the apparatus and methods of the present disclosure may be utilized to improve upon the
2 conventional connector designs to create an even smaller fiber optic connector for
3 maximum density installations.

4 It will be apparent to one of skill in the art that described herein is a novel fiber
5 optic connector and a novel method for achieving a high-density fiber optic installation
6 using said connectors. A latch pull mechanism is provided such that movement of the
7 latch pull relative to the connector body acts to decouple the latch mechanism, and thus
8 the fiber optic connector, from a fiber optic receptacle. While the invention has been
9 described with references to specific preferred embodiments, it is not limited to these
10 embodiments. Although the embodiments described herein relate to fiber optic systems,
11 one of skill in the art can appreciate that the disclosed subject matter can be utilized with
12 any form of communication device or system. The invention may be modified or varied
13 in many ways and such modifications and variations as would be obvious to one of skill
14 in the art are within the scope and spirit of the invention and are included within the
15 scope of the following claims.